

1.9 5650 – 5850 MHz Bandplan

Frequency	Maximum Bandwidth	Mode	Usage
5650.000	2700 Hz	ALL MODES	AMATEUR SATELLITE SERVICE (up-link)
5668.000			
5668.000	2700 Hz	ALL MODES	5668.200 Narrow band center of activity (a)
5670.000			AMATEUR SATELLITE SERVICE (up-link)
5670.000		MGM	
5700.000			
5700.000		ATV	
5720.000			
5720.000		ALL MODES	
5760.000	2700 Hz	ALL MODES	5760.200 Narrow band center of activity (a)
5760.000			5760.750-5760.800 Local Beacon (d)
5760.800		Telegraphy MGM	BEACONS ONLY
5760.990			
5761.000		ALL MODE	
5762.000			
5762.000		ALL MODES	(d)
5830.000			
5830.000		ALL MODES	AMATEUR SATELLITE SERVICE (down-link)
5850.000			

1.9.1 Notes: BANDPLAN

Footnotes

- Societies are urged to inform their members that stations should preferably be able to operate in both narrow-band segments.
- 5760.750-5760.800MHz may be designated for Local Beacon use (10W ERP max) by National Societies.
- Refer to Beacons Chapter for coordination of beacons in the beacon sub-band
- Any wideband system shall protect narrowband applications, which have priority